



MULTI-PURPOSE - 2

Premium Lithium Based Grease

TECHNICAL DATA SHEET

Product Description

Veedol Multi-Purpose-2 is high quality lithium based grease, processed from premium high viscosity virgin base oils and performance additives having NLGI-2 consistency. It is recommended for heavily loaded anti-friction wheel bearings, universal joints and chassis.

Features/Benefits

- Ensures extended life of the bearings.
- Outstanding oxidation and thermal stability.
- Imparts excellent rust inhibition.

Typical Properties

Test Parameters	Units	ASTM Method	Typical Values
Thickener base			Lithium
Base Oil			Mineral
NLGI consistency			2
Penetration @ 25 ° C, unworked		ASTM D 217	276
worked 60st		ASTM D 217	278
Drop point	°C	ASTM D 2265	195
Timken Ok Load	Kg	ASTM D 2509	45
Rust prevention(1425 rpm/50 Hz)		ASTM D 1743	PASS
Work stab(10000st - 60st)	units	ASTM D 217	2
Viscosity @ 40 ° c	cSt	ASTM D 445	160
Viscosity @ 100 ° c	cSt	ASTM D 445	15.2
Roll stability	%	ASTM D 1831	2
Water wash out @ 80° C	% mass	ASTM D 1264	3
Copper Corr- 24 h@100°C		ASTM D 4048	0

Properties mentioned above are typical only, and minor variations which do not affect the product performances, are to be expected in normal manufacturing.

فيدول إنترناشيونال د.م.س.س

VEEDOL INTERNATIONAL DMCC

وحدة رقم 601 | إنديغو آيكون | أرض رقم إف 3 | أبراج بحيرات الجميرا | دبي | الامارات العربية المتحدة | تليفون: +971 4 3688 416 | فاكس: +971 4 3688 418
Unit No. 601 | Indigo Icon | Plot No. F3 | Jumeirah Lakes Towers | P.O. Box No. 117019 | Dubai | United Arab Emirates
رقم الرخصة ٣٢٠٥١ DMCC | رقم السجل التجاري ٣٠٠٢ DMCC
Tel: +971 4 3688 416 | Fax: +971 4 3688 418 | Email: office@veedol.ae | www.veedol.ae