



TECHNICAL DATA SHEET

Elite 10W-30

Premium High Performance Multigrade Petrol Engine Oil

Product Description

Veedol **Elite 10W-30** is meticulously formulated from premium quality virgin base oils to bring out the best engine performance of new generation vehicles. It provides excellent sludge and deposit control. A robust anti-friction additive helps protect the engine parts on cold starts and resists oil degradation throughout the recommended oil drain interval.

Performance Specification

Veedol Elite 10W-30 meets or exceeds performance requirements:

API: SL/CF

Features & Benefits

- Suitable for American, European and Japanese vehicles
- Keeps the engine clean for a smoother and powerful ride
- Very High Viscosity Index retains outstanding fluidity at low temperature (sub-zero) and high viscosity at high operating temperatures to completely eliminate metal to metal contact over wide operating conditions
- · Very high thermal and oxidation stability ensures longer oil drain intervals
- Provides optimum cooling and helps achieve high engine efficiency
- · Manufactured from Virgin Base Oil

Typical Properties

Test Parameters	ASTM Method	Typical Values
Density @15°C	D4052	0.864
Kinematic Viscosity @100°C, cSt	D445	10.8
Viscosity Index	D2270	141
Total Base Number, mg KOH/gm	D2896	8.0
Pour Point, °C	D97	-36
Flash Point (COC), °C	D92	230

^{*}Properties mentioned above are typical only, and minor variation which do not affect the product performance, are to be expected in normal manufacturing.

www.veedol.ae Find the best oil for your vehicle @ www.veedol.ae/lube-advisor

This information may contain proprietary, confidential or privileged data or any matter which is subject to Intellectual Property Rights owned by Veedol International Ltd.

