

Diesel Engine Oils



TECHNICAL DATA SHEET

HDC 10W

Heavy Duty Diesel Engine Oil

Product Description

Veedol HDC 10W is suitable for use in naturally aspirated and turbocharged diesel engines. It exceeds requirements of API CF/SF and can also be used as hydraulic oil in off highway equipments requiring API CF/SF SAE 10W Oil.

Performance Specification

Veedol HDC 10W meets the performance requirements of the following:

API: CF/SF

Features & Benefits

- Its unique detergent-dispersant additive system removes and keeps all contaminants like soot/sludge in highly dispersed state to protect engine from abrasive and corrosive wear over longer drain intervals.
- Processed from premium quality virgin base oils, it provides optimum cooling to all engine components.

Typical Properties

Test Parameters	ASTM Method	Typical Values
Density @15°C	D4052	0.882
Kinematic Viscosity @100°C, cSt	D445	6.4
Viscosity Index	D2270	101
Total Base Number, mg KOH/gm	D2896	11.5
Pour Point, °C	D97	-39
Flash Point (COC), °C	D92	210

*Properties mentioned above are typical only, and minor variation which do not affect the product performance, are to be expected in normal manufacturing.

www.veedol.ae

Find the best oil for your vehicle @ www.veedol.ae/lube-advisor

This information may contain proprietary, confidential or privileged data or any matter which is subject to Intellectual Property Rights owned by Veedol International Ltd.



Ford Model T



Nürburgring



Africa Eco Race