

Diesel Engine Oils



TECHNICAL DATA SHEET

MAX-PRO DH-1 15W-40

High Performance Multi-Grade Engine Oil

Product Description

Veedol **Max-Pro DH-1** is a high performance diesel engine oil specially developed to handle the increased demands of low emission engines. Its unique additive technology ensures high temperature detergency and clean engine components. It is designed with excellent anti-wear and anti-oxidation agents that ensures longer life for the oil.

Application

Veedol Max-Pro DH-1 engine oil is recommended for use in diesel engines of heavy duty earthmoving equipments operating under severe conditions.

Performance Specification

Veedol Max-Pro DH-1 meets and exceeds the following performance requirements:
API CI-4/CH-4/SL/SJ | ACEA E7-12/E7-16 | MB 228.3 | MAN 3275 | Volvo VDS-3 | Deutz III 10 | MTU 2.0 | MACK EO-N+ | MACK EO-N | CES 20076/20077/ 20078 | Caterpillar ECF-1a | Renault RLD-2 | JASO DH-1 | Global DHD-1 | Detroit DDC 93K215

Features & Benefits

- Reduces piston deposits.
- Reduces Engine wear.
- Ensures maximum protection for engine components under severe conditions.

Typical Properties

Test Parameters	ASTM Method	Typical Values
Density @15°C	D4052	0.88
Kinematic Viscosity @100°C, cSt	D445	15.0
Viscosity Index	D2270	136
Total Base Number, mg KOH/gm	D2896	13
Pour Point, °C	D97	-33
Flash Point (COC), °C	D92	234

*Properties mentioned above are typical only, and minor variation which do not affect the product performance, are to be expected in normal manufacturing.

www.veedol.ae

Find the best oil for your vehicle @ www.veedol.ae/lube-advisor

This information may contain proprietary, confidential or privileged data or any matter which is subject to Intellectual Property Rights owned by Veedol International Ltd.



Ford Model T



Nürburgring



Africa Eco Race