



POWERTRON 5W-20/ 5W-30

Synthetic Blend Petrol Engine Oil

Product Description

Veedol Powertron 5W-20 / 5W-30 are premium high-performance Synthetic blend multigrade engine oils engineered with latest in lubricant additive technology suitable for use in passenger cars and commercial vehicles requiring the specification of 5W-20 or 5W-30.

Performance Specification

Veedol Powertron 5W-20/ 5W-30 meets and exceeds the following performance requirements:
API SN+/SN/SL | ILSAC – GF-5

Features & Benefits

- Excellent performance and engine protection at high & low temperatures.
- Improved fuel efficiency.
- Ensured oil performance and reduced consumption.
- High level of internal engine cleanliness.
- Lower Emissions.
- Recommended for TGDI and Hybrid engines.
- Superior protection against sludge formation and combustion contamination.



Typical Properties

Test Parameters	ASTM Method	Typical Values	
		5W-20	5W-30
Density @15°C	D4052	0.86	0.85
Kinematic Viscosity @100°C, cSt	D445	8.7	9.8
Viscosity Index	D2270	155	170
Total Base Number, mg KOH/gm	D2896	7.5	8.1
Pour Point, °C	D97	-43	-43
Flash Point (COC), °C	D92	225	230

*Properties mentioned above are typical only, and minor variation which do not affect the product performance, are to be expected in normal manufacturing.



Ford Model T



Nürburgring



Africa Eco Race