

Passenger Car Motor Oils



TECHNICAL DATA SHEET (TDS)

SYNTRON 5W-40

Fully Synthetic Petrol Engine Oil

Product Description

Veedol **Syntron 5W-40** is a fully synthetic engine oil for today's high performance engines, including multi-valve, fuel injection and turbocharged petrol and diesel engines where specified. This oil is not suitable for vehicles that have exhaust after treatment devices fitted.

Performance Specification

Veedol Syntron 5W-40 meets and exceeds the following performance requirements:
API SN | ACEA A3/B4 | MB 229.3/229.5/226.5 | BMW LL-01 | Renault RN0700/RN0710
PSA: B71 2296 | Porsche: A40

Features & Benefits



- Ensures lubricant performance over extended drain intervals
- Excellent high & low temperature performance.
- Outstanding fuel efficiency.
- Effective environmental protection.
- High Level of engine cleanliness

Typical Properties

Test Parameters	ASTM Method	Typical Values
Density @15°C	D4052	0.85
Kinematic Viscosity @100°C, cSt	D445	14.1
Viscosity Index	D2270	157
Total Base Number, mg KOH/gm	D2896	10.6
Pour Point, °C	D97	-42
Flash Point (COC), °C	D92	225

*Properties mentioned above are typical only, and minor variation which do not affect the product performance, are to be expected in normal manufacturing.

www.veedol.ae

Find the best oil for your vehicle @ www.veedol.ae/lube-advisor

This information may contain proprietary, confidential or privileged data or any matter which is subject to Intellectual Property Rights owned by Veedol International Ltd.

