



UNITRAC 15W-40

High Performance Universal Tractor Oil

Product Description

Veedol **Unitrac 15W-40** is Universal Tractor Oil (STOU) designed for a wide variety of applications for modern Agriculture equipments. It is a fine blend of high viscosity index base oils and an advanced additive package designed to give reliable performance in a wide range of farming applications.

Performance Specification

Veedol Unitrac 15W-40 meets and exceeds performance requirements of:

- **Engine:**
API CG-4/CF-4/CF/CE-SF/CD-SF | ACEA E3 | MB 227.1 | MB 228.1
- **UTTO/Transmission:**
John Deere J20C/J20D | Ford M2C86B/C - M2C 134D | JI Case/Case Int : MS-1204/6/7/9 | CNH MAT 3525/3526 | Massey Ferguson M 1135/43/45 | Caterpillar TO-2 | API GL-4 | Allison C-4
- **STOU:**
ZF-TE-ML 06A/06B/06C/07B | Ford M2C 159B/C | Ford New Holland 82009201/2/3 | Massey Ferguson M1139/1144/1145 | John Deere J27
- **Hydraulic:**
Sperry Vickers/Eaton: I-280-S | Sperry Vickers/Eaton: M2950S | Sauer Sunstand/Danfoss: Hydrostatic Hyd Fluid
- **Wet Brakes Specs: Suitable for Wet Brakes**

Features & Benefits

- Single product that protects engine, transmission, wet brake, hydraulic and front axles
- Improved performance, superior extended machine life & reduced downtime
- Suitable for wide range of manufactures
- Suitable for use in Manual, Powershifts, CVTs and Hydrostatic Drives
- Reduces inventory & cuts downs cost



Ford Model T



Nürburgring



Africa Eco Race



UNITRAC 15W-40

High Performance Universal Tractor Oil

Typical Properties

| Test Parameters | ASTM Method | Typical Values |
|---------------------------------|-------------|----------------|
| Density @15°C | D4052 | 0.885 |
| Kinematic Viscosity @100°C, cSt | D445 | 14.5 |
| Viscosity Index | D2270 | 140 |
| Total Base Number, mg KOH/gm | D2896 | 10.5 |
| Pour Point, °C | D97 | -36 |
| Flash Point (COC), °C | D92 | 224 |

*Properties mentioned above are typical only, and minor variation which do not affect the product performance, are to be expected in normal manufacturing.

