



UNITRANS 80W

High Performance Universal Transmission Fluid (UTTO/THF)

Product Description

Veedol **Unitrans 80W** is a universal oil for transmission and hydraulic system of tractors equipped with oil immersed brakes.

Performance Specification

Veedol Unitrans 80W meets and exceeds performance requirements of:

API GL-4 | Ford M2C134D/M2C86-B | John Deere J-20C/D | Massey Ferguson CMS M 1145 |
Massey Ferguson M1135/M1141/0M1143 | Case MS 1204/1206/1207/1209 |
CNH MAT 3525/3526 | Parker (Denison UTTO/HF-0/HF-02) |
Eaton Vickers (Mobile Hydraulic System - Brochure 694) | Sperry Vickers/Eaton I-280-S |
Allison C-4 | CAT TO-2 | KUBOTA UDT | JCMAS HK P-041

Features & Benefits

- Ensures longer transmission life
- Protects against rust & corrosion
- Excellent wet clutches and wet brake performance
- Reduces brake noise
- Higher oxidation stability and thermal resistance
- Offers excellent seal compatibility and possesses good anti-foam properties





UNITRANS 80W

High Performance Universal Transmission Fluid (UTTO/THF)

Typical Properties

Test Parameters	ASTM Method	Typical Values
Density @15°C	D4052	0.880
Kinematic Viscosity @100°C, cSt	D445	9.0
Viscosity Index	D2270	135
Pour Point, °C	D97	-36
Flash Point (COC), °C	D92	220

*Properties mentioned above are typical only, and minor variation which do not affect the product performance, are to be expected in normal manufacturing.

