



DIESEL STAR PLUS 15W-40

High Performance Multigrade Engine Oil For Turbocharged Diesel Engines

Product Description

Veedol Diesel Star Plus 15W-40 is a high performance diesel engine oil for modern generation turbocharged/ supercharged automobile/ industrial/ Off-Highway diesel engines.

Performance Specification

Veedol Diesel Star Plus meets and exceeds the following performance requirements:
**API CH-4/SL | ACEA E7-08 Issue 2 | MB 228.3 | MAN 3275 | Volvo VDS-3 |
MTU Type 2 | MACK EO-M+ EO-N | CUMMINS CES 20076/20077 |
Caterpillar ECF-1a | Renault RLD-2 | Detroit DDC 93K215**

Features & Benefits



- Higher Detergency/Dispersion oil offers HI-TECH BENEFITS with outstanding engine cleanliness for much longer period
- Helps achieve higher fuel efficiency, longer engine durability and lower emissions
- High Viscosity Index (HVI) Oil retains optimum viscosity which helps to eliminate metal to metal contact even in severe heavy-duty high temperature operating conditions
- Oil with very high thermal and oxidation stability which helps to achieve longer drain intervals
- Recommended for use in heavy duty engines such as Mercedes Benz, Volvo, Scania, MAN, Mitsubishi Fuso, IVECO, GM, Hino, Cummins, Perkins, Caterpillar, Komatsu, etc. used in Trucks, Buses, Industrial and Off-Highway equipments.
- Veedol Diesel Star Plus 15W-40 is suitable for the vehicles requiring API CH-4 engine oil

 www.veedol.ae

Find the best oil for your vehicle @ www.veedol.ae/lube-advisor

This information may contain proprietary, confidential or privileged data or any matter which is subject to Intellectual Property Rights owned by Veedol International Ltd.



Ford Model T



Nürburgring



Africa Eco Race

Diesel Engine Oils



TECHNICAL DATA SHEET

DIESEL STAR PLUS 15W-40

High Performance Multigrade Engine Oil For Turbocharged Diesel Engines

Typical Properties

Test Parameters	ASTM Method	Typical Values
Density @15°C	D4052	0.878
Kinematic Viscosity @100°C, cSt	D445	14.8
Viscosity Index	D2270	136
Total Base Number, mg KOH/gm	D2896	10.5
Pour Point, °C	D97	-33
Flash Point (COC), °C	D92	236

*Properties mentioned above are typical only, and minor variation which do not affect the product performance, are to be expected in normal manufacturing.



Ford Model T



Nürburgring



Africa Eco Race