



Syntron TGDI 0W-20

Advanced Fully Synthetic Modern Generation Engine Oil (Anti LSPI)

Product Description

Veedol Syntron TGDI 0W-20 oil is an advanced fully synthetic modern generation engine oil specially formulated for latest generation high performance passenger cars equipped with Turbocharged Gasoline Direct Injection (TGDI), GDI and hybrid engines. Veedol Syntron TGDI 0W-20 oil is blended with advanced technology additive system which exceeds the requirement of sequence IX engine test for LSPI (Low Speed Pre-Ignition), critical requirement for performance in TGDI engines. Veedol Syntron TGDI 0W-20 oil with its robust Engine Care Technology (ECT) provides enhanced protection to emission control system and seals, employed in latest generation passenger car engines and delivers improved fuel economy.


Performance Specification

Veedol Syntron TGDI 0W-20 meets and exceeds performance requirements of: **API SP | ILSAC GF-6**



Features & Benefits

- Effective protection against LSPI events, with special formulation
- Better sludge and deposit control for improved turbocharger cleanliness and extended service life
- Stable viscosity provides optimum film thickness at all operating temperature range
- Excellent thermal and oxidation stability for prolong service life
- Excellent low temperature properties provides easy cold start and prevents wear
- Enhances fuel economy and improves engine power
- Helps to achieve optimum engine performance and ensure protection for longer drain interval
- Better aeration control
- Aid to minimize exhaust emissions
- Recommended for all modern generation cars such as American, European, Japanese, Korean etc. requiring API SP grade oil





Syntron TGDI 0W-20

Advanced Fully Synthetic Modern Generation Engine Oil (Anti LSPI)

Application

1. Recommended for use in TGDI/ GDI/ Hybrid/ DOHC/ VVTI/ Turbocharged, supercharged and all naturally aspirated engines.
2. Suitable for use in all modern generation cars such as Toyota, Honda, Suzuki, Hyundai, Kia, Mercedes Benz, BMW, Audi, VW, Fiat, Ford, GM, Chrysler etc.

Typical Properties

Test Parameters	ASTM Method	Typical Values
Density @15°C	D4052	0.8424
Kinematic Viscosity @100°C, cSt	D445	8.423
Viscosity Index	D2270	170
Total Base Number, mg KOH/gm	D2896	8.2
Pour Point, °C	D97	-42
Flash Point (COC), °C	D92	>200
CCS Viscosity @-35°C, mPa.s	D5293	5470

*Properties mentioned above are typical only, and minor variation which do not affect the product performance, are to be expected in normal manufacturing.

