

Specialties & Other Fluids



TECHNICAL DATA SHEET

TRACTOR OIL 10W-30

Multi Functional Oil For Tractors And Off-Road Equipments

Product Description

Veedol **Tractor Oil 10W-30** is a premium "Super Tractor Oil Universal" (STOU) specially formulated for use in engine, hydraulic systems, oil immersed brakes & transmissions of tractors and off-road equipments.

Performance Specification

Veedol Tractor Oil 10W-30 meets and exceeds performance requirements of:

- **Engine:**
API CG-4/CF-4/CF/CE-SF/CD-SF | ACEA E3 | MB 227.1 | MB 228.1
- **UTTO/Transmission:**
John Deere J20C/J20D | Ford M2C86B/C - M2C 134D | JI Case/Case Int : MS-1204/6/7/9 | CNH MAT 3525/3526 | Massey Ferguson M 1135/43/45 | Caterpillar TO-2 | API GL-4 | Allison C-4
- **STOU:**
ZF-TE-ML 06A/06B/06C/07B | Ford M2C 159B/C | Ford New Holland 82009201/2/3 | Massey Ferguson M1139/1144/1145 | John Deere J27
- **Hydraulic:**
Sperry Vickers/Eaton: I-280-S | Sperry Vickers/Eaton: M2950S | Sauer Sunstand/Danfoss: Hydrostatic Hyd Fluid
- **Wet Brakes Specs:** Suitable for Wet Brakes

Features & Benefits

- Maintains engine cleanliness
- Maximize transmission life
- Gear protection
- Excellent hydraulic system performance
- Provides smooth wet brake and clutch operation
- Protects against rust and corrosion

 www.veedol.ae

Find the best oil for your vehicle @ www.veedol.ae/lube-advisor

This information may contain proprietary, confidential or privileged data or any matter which is subject to Intellectual Property Rights owned by Veedol International Ltd.



Ford Model T



Nürburgring



Africa Eco Race

© Veedol International DMCC. All rights reserved.

*Registered trademarks of Veedol International UK.

Specialties & Other Fluids



TECHNICAL DATA SHEET

TRACTOR OIL 10W-30

Multi Functional Oil For Tractors And Off-Road Equipments

Typical Properties

Test Parameters	ASTM Method	Typical Values
Density @15°C	D4052	0.86
Kinematic Viscosity @100°C, cSt	D445	11
Viscosity Index	D2270	150
Total Base Number, mg KOH/gm	D2896	10.5
Pour Point, °C	D97	-39
Flash Point (COC), °C	D92	230

*Properties mentioned above are typical only, and minor variation which do not affect the product performance, are to be expected in normal manufacturing.

 www.veedol.ae

Find the best oil for your vehicle @ www.veedol.ae/lube-advisor

This information may contain proprietary, confidential or privileged data or any matter which is subject to Intellectual Property Rights owned by Veedol International Ltd.



© Veedol International DMCC. All rights reserved.

*Registered trademarks of Veedol International UK.